

ST-1322/2
STB-1432/2

Double Chamber Forced Air Tunnels



MADE IN U.S.A

Distributed by:

shorr | packaging corp.
shorr.com 888.885.0055

Features, Functions & Benefits

- Continuous duty industrial grade blower motor
- Air velocity control
- Top/bottom adjustable air control dampers for controlled shrink results
- Easy to read L.E.D. display
- Cool-Touch energy efficient design
- AC motor with variable speed control for conveyor speed
- Air velocity control for the adjustment of air flow to the top or bottom of the package for even shrink
- Audible high heat alarm and high heat limit thermostat
- Stainless steel mesh belt
- Durable powder coat finish
- Various Belt options available

Specifications:	ST-1322/2	STB-1432/2		ST-1322/2	STB-1432/2
Opening:	13" H x 22"W	14"H x 32"W	A =	85"	111"
Electrical:	240V, 65 amp, 3 phase	480V, 67 amp, 3 phase	B =	34.6"	42.25"
Heaters:	6 flange cal-rod types	6 flange cal-rod types	C =	132.8"	158.8"
Conveyor Height:	Adj. from 33" to 37-1/2"H	Adj. from 30-1/2" to 36"H	D =	79" min. (allow 96")	80" min. (allow 96")
Conveyor Width:	15"	24"	E =	30" min.	30-1/2" min
Chamber Length:	85"	111"	F =	44"	54.5"
Conveyor Speed:	0-160 FPM	0-160 FPM			
Shipping Weight:	1,820 lbs	2,000 lbs			

