



"Speed, Flexibility, Dependable Performance"

ST-1322
STB-822M
ST-1432

Single Chamber
Forced Air Tunnels



MADE IN U.S.A

Distributed by:



TEXWRAP®

Features, Functions & Benefits

- Continuous duty industrial grade blower motor
- Easy to read L.E.D. display
- Cool-Touch energy efficient design
- AC motor with variable speed control for conveyor speed
- Top air velocity control for the adjustment of air flow to the top or bottom of the package for even shrink
- Audible high heat alarm and high heat limit thermostat
- Stainless steel mesh belt
- Durable powder coat finish
- Various belt options available
- Automatic cool down

Specifications:	ST-1322	STB-822M	ST-1432
Opening:	13"H x 22"W	8"H x 22"W	14"H x 32"W
Electrical:	230V/3phase/36 amps	230V/3phase/34 amps	230V/3phase/50 amps
Heaters:	3 flange cal-rod types	3 flange cal-rod types	3 flange cal-rod types
Conveyor height:	adj. 30" - 35"H	adj. 30" - 35"H	adj. 30" - 35"H
Conveyor speed:	0 -100 FPM	0 -150 FPM	0 -150 FPM
Machine dimensions:	58"L x 45"W x 74-79"H	112"L x 46"W x 74-79"H	103.5"L x 55"W x 74-79"H
Shipping weight:	826 lbs	1,150 lbs	1,050 lbs
Conveyor width:	15"	15"	24"
Chamber Length:	42-1/4"	64"	55"

	A	B	C	D	E	F
ST-1322	3' 6-1/4"	2' 10-3/4"	4' 10"	6' 2"	2' 6"	3' 10"
STB-822M	5' 4"	2' 10-5/8"	9' 4"	6' 2"	2' 6"	3' 10"
ST-1432	4' 7"	3' 8-1/2"	6' 1"	6' 7"	2' 6"	4' 8"

