



"Speed, Flexibility, Dependable Performance"

ST-2010

Intermittent Side Seal Wrapper

Compact 2-belt design

Flexible

Big capacity

Easy operation



The ST-2010 is Texwrap's offering for applications requiring the wrapping of products at moderate speed where product length or height exceeds the capacity of an L-sealer. The 2010 has a big product handling capacity capable of wrapping products up to 10" high and up to 20" wide and, with film/conveyor speeds of 100 feet per minute, the 2010 has plenty of speed to handle a variety of applications.

The 2010's 2-belt design means that the end seal is made prior to the side seal. This design allows the ST-2010 to fit in the space of an L-sealer but also requires the product to be spaced apart prior to entering the infeed conveyor.

The ST-2010 is easy to use, rugged enough for constant operation, and comes standard with premium features not available on competitive models in this price range including low-mount film cradle, touchscreen library to easily recall package setups, and automatic dwell time compensator. Allen-Bradley controls, restricted service-level menus, and AC VFD drives make the 2010 as popular with maintenance staffs as with operators.

Made in USA

Distributed by:



TEXWRAP®

Features:

- Large product size capacity
- Allen-Bradley controls
- Maximum film capacity: 32" CF
- Texwrap Round Seal side seal
- Easy change-over "tool-less" set up
- Color touchscreen with set-up product memory & machine diagnostics
- Upstream / downstream handshaking, quick connect cable system for additional equipment
- Welded tubular construction with powder coat finish
- Internal scrap take up with film break and take up reel alarms
- Sensorless vector AC drives
- Fully guarded

Specifications:

Maximum package size: 10"H x 20"W x infinite length
(maximum dimensions cannot be combined)

Minimum package size: 4"L x 2"W (standard)
2"L x 2"W (with closing conveyor)

Conveyor width: 20"

Cross seal width: 24"

Cross seal drive: Pneumatic

Maximum film width: 32" centerfolded

Electrical requirements: 208/240 Vac, 1 phase, 18/15 amps

Air requirements: 80 PSI, 5CFM

Conveyor height: 32" to 37"

Maximum film speed: 100 FPM

Operator control panel: Color touch screen

